



Rapid Imaging Solvent Management RI 80 Continuous Feed Recovery Unit Requires Less User Intervention

The RI 80 Solvent Recycler features rapid-start direct electric heating of solvent and a short cool-down time due to high-efficiency condensers and air cooling with a motor driven fan.

- › RI80 Continuous Feed is our largest unit
- › Recycles one 55 gallon drum per day
- › This unit runs continuously, automatically refills itself as needed
- › Average recycle time to run one 55 gallon drum is 18-20 hours, start to finish
- › Solvent Transfer: Auto-transfer, in and out
- › Heater: Explosion Proof, Sealed, Direct Heating
- › Heater: 5000 Watts
- › Power Supply: 220 Volts, 30 Amp, single-phase, Air 100 psi
- › Footprint: 47"x27"x50" (WDH)
- › Weight: 460 lb
- › Requires less user intervention

Customer Advantages for In-House Distillation

1. Units are very small
2. Extremely simple to run
3. ROI is less then one year in most instances
4. 95% reduction in drum handling, no more moving drums in and out of your facility
5. The dirty drums never moves
6. 90% recovery rate, meaning the clean drum is replaced approximately every 10 cycles.
7. No more waiting for distilled solvent
8. No more shipping costs for dirty solvent
9. Improves plate quality by running cleaner
10. Improves productivity
11. Environmentally friendly

Work Flow for Distillation Units

A sophisticated micro-processor controls the work flow described below.

1. Used solvent is transferred to the distillation tank of the recycler.
2. Heat from the heating element vaporizes the solvent, leaving the residue in the tank for later removal.
3. Clean recycled solvent vapor cools as it flows through the air cooled condenser to the receiving container.
4. Clean recycled solvent is transferred to a drum for reuse.

For more information, please contact us at:

3005 Chastain Meadows Pkwy, Marietta, GA 30066

p 770.420.4006 * 800.464.2931 * f 770.420.2952

info@jvisinc.com * www.jvis-flexo.com

